

		BG1000A series(Wall-mount) / SERIE BG1000A (a parete)			
		32BG1000A	43BG1000A	49BG1000A	55BG1000A
					
Panel Parameters	Resolution	1366*768	1920*1080		
	Screen Ratio	16: 9			
	Visual Angle	85/85/85/85			
	Refresh frequency	60Hz	60Hz	60Hz	60Hz
	Life Time	30000H	30000H	30000H	30000H
	Static contrast ratio	2400:1	1000:1	4000:1	4000:1
	Response speed	6.5ms	12ms	12ms	12ms
	Max Brightness	350cd/m <sup>2</sup>			
Core Parameters	Chip	Dual core A53 processor\Quad core GPU\Dominant frequency: 1.2GHz			
	OS	Android 4.4.2			
	CPU	Dual core A53 processor			
	System memory	1G DDR3			
	Hard disk storage	8G			
Interface Setting	USB2.0	1			
	USB3.0	1			
	Earphone	1			
	LAN	1			
	TF Cassette	1			
	HDMI 2.0	1			
Basic functions	Horizontal and vertical display	yes	yes	yes	yes
	Timing switch	yes	yes	yes	yes
	USB data input	yes	yes	yes	yes
	Cable network	yes	yes	yes	yes
	Wireless Wi-Fi	yes	yes	yes	yes
	Speaker Power	2*5W	2*5W	2*5W	2*5W
	Quantity of speaker	2	2	2	2
Interactive Device	Media Info Display	Support videos splitting, subtitle rolling, switch timing and USB data input			
	Release System in Background (Option)	Support Program management/ Terminal management/ News making/ Program making			
	Video Decoding	3GP, 3G2, AVI,FLV,F4V,OGG,MP4,MOV,TS,M2TS,M2T,M2P,MKV.1920*1080 30Hz			
	Picture Format	jpeg, png, gif, bmp.			
CBU Craft	CBU material	Metal/ aluminum			
	Frame material	aluminum			
	CBU color	Black	Black	Black	Black
	Frame color	Silver	Silver	Silver	Silver
	Frame Size	21.9mm	22.7mm	22.7mm	22.7mm
	CBU Thickness	17.6mm	21.5mm	21.5mm	21.5mm
	Distance Between Installing Holes	400*200	400*200	400*200	400*200
	Quantity of Installing Holes	6	6	6	6
Power	Rated Power Consumption	75W	96W	100W	125W